

Sweepers

Commercial Equipment



Terra® 26M

Walk-Behind Push Sweeper

- 26 inch sweep path
- Manually operated
- Tools-free adjustable side brooms
- Tools-free adjustable rear main broom
- Dual caster wheels operate in the “clean path” behind side brooms
- Variable handle height
- Handle folds down



Terra® 28B

Walk-Behind Sweeper

- 28 inch sweep path
- Maintenance free gel battery standard
- Half as loud as most vacuums at 59 dB A
- Standard onboard battery charger
- Tools-free removable brooms and hopper
- Rugged construction for carpet or hard floor applications



Terra® 132B

Walk-Behind Sweeper

- 32 inch sweep path
- Battery operated
- Standard onboard battery charger
- Tools-free removable brushes and hopper
- Rugged construction for carpet or hard floor applications



Terra® 4300B

Rider Sweeper

- 46 inch sweep path, battery operated
- Simple, ergonomic and intuitive operator interface
- 20% gradeability while sweeping
- Rugged construction for carpet or hard floor applications



Smart cleaning.

A Nilfisk-Advance Brand

Technical Specifications

Models	Terra® 26M	Terra® 28B	Terra® 132B	Terra® 4300B
Sweep Path	26 in (66 cm)	28 in (71 cm)	32 in (81 cm)	46 in (117 cm)
Max Productivity -per hour	28,600 ft ² /hr (2,650 m ² /hr) @ 2.5 mph (4 kph)	31,200 ft ² (2,900 m ²) @ 2.5 mph (4 kph)	39,424 ft ² (3,662 m ²) @ 2.8 mph (4.50 kph)	60,720 ft ² (5,640 m ²) @ 3 mph (4.8 kph)
Sweeping Principle	Over-Throw	Direct-Throw	Over-Throw	Over-Throw
Main Broom Sweep Path	26 in (66 cm)	19.7 in (50 cm)	24 in (61 cm)	28 in (71.12 cm)
Side Broom(s)	(2) 10 in (25 cm) Dia. Right & Left	(1) 12.4 in (31.5 cm) Dia. Right Side	(1) 14 in (36 cm) Dia. Right Side	(2) 16.5 in (42 cm) Dia. Right & Left
Power Source	Manual	1) 12 V, 86 Ah maintenance free gel batt	(2) 6 V batteries - onboard battery charger	(4) 6 V batteries onboard battery charger
Main Broom Speed	-	335 rpm	400 rpm	550 rpm
Main Broom/ Traction Motor	-	0.3 hp (200 W)	0.8 hp (600 W)	0.8 hp (600 W) traction motor only
Hopper Capacity	1.2 ft ³ (34 L)	2.1 ft ³ (60 L)	1.74 ft ³ (49 L)	2.5 ft ³ (70 L)
Filtration System	-	10.8 ft ² (1 m ²) polyester panel filter	27 ft ² (2.5 m ²) area pleated filter w/ carpet pre-filter	54 ft ² (5 m ²) area pleated filter w/ carpet pre-filter
Length	51 in (130 cm)	39 in (99 cm)	42 in (107 cm)	58 in (148 cm)
Width	32 in (82 cm)	31.5 in (80 cm)	30.5 in (77 cm)	36.6 in (93 cm)
Height	40.5 in (103 cm)	24.4 in (62 cm)	33 in (84 cm)	48 in (122 cm)
Weight	35 lb (16 kg)	171 lb (77.5 kg)	342 lb (155 kg)	562 lb (255 kg)

Specifications are subject to change without notice.



©2011 Nilfisk-Advance, Inc. Form L1610A 12-8-11

14600 21st Avenue North
Plymouth, MN 55447-3408
www.advance-us.com
Phone 800-850-5559
Fax 800-989-6566

240 Superior Boulevard
Mississauga, Ontario, Canada L5T 2L2
www.nilfisk-advance.com
Phone 800-668-8400
Fax 800-263-5111

