

A Series High Range Stand-on Pallet Stacker With Reach Fork

Distinguishing marks	HANGCHA GROUP CO.,LTD.			
	1.1	Manufacturer	CQDB12-AC1S-J	CQDB16-AC1S-J
1.2	Manufacturer's type designation	CQDB12-AZ3S-J	CQDB16-AZ3S-J	
1.3	Drive: electric (battery or mains), diesel, petrol, fuel gas	Electric	Electric	
1.4	Operator type: hand, pedestrian, standing, seated, order-picker	Standing	Standing	
1.5	Rated capacity/rated load	Q (kg)	1200	
1.6	Load centre distance	c(mm)	600	
1.8	Load distance, centre of drive axle to fork	x (mm)	442	
1.9	Wheelbase	y (mm)	1384	
2.1	Service Weight	kg	1870	
3.1	Tyres: solid rubber, superelastic, pneumatic, polyurethane		Polyurethane	
3.2	Tyre size, front	mm	φ230×75	
3.3	Tyre size, rear	mm	φ100×70	
3.5	Wheels, number front / rear (x = driven wheels)		1×/4	
3.6	Tread, front	b10 (mm)	0	
3.7	Tread, rear	b11 (mm)	1170	
4.1	Tilt of fork carriage forward/backward	α/β(°)	3/5	
4.2	Height, mast lowered	h1 (mm)	2040	
4.4	Lift	h3 (mm)	2700	
4.5	Height, mast extended	h4 (mm)	3752	
4.8	stand height	h7 (mm)	185	
4.10	Height of wheel arms	h8 (mm)	130	
4.19	Overall length	l1 (mm)	2295	
4.20	Length to face of forks	l2 (mm)	1225	
4.21	Overall width	b1/b2 (mm)	800/1270	
4.22	Fork dimensions	s/e/l (mm)	35/100/1070	
4.24	Fork-carriage width	b3 (mm)	920	
4.25	Distance between fork-arms	b5 (mm)	200-896	
4.26	Distance between wheel arms	b4 (mm)	1070	
4.28	Reach distance	l4 (mm)	590	
4.32	Ground clearance, centre of wheelbase	m2 (mm)	70	
4.34.1	Aisle width for pallets 1000 x 1200 crossways	Ast (mm)	2701	
4.34.2	Aisle width for pallets 800 x 1200 lengthways	Ast (mm)	2739	
4.35	Turning radius	Wa (mm)	1682	
4.37	Length across wheel arms	l7 (mm)	1794	
5.1	Travel speed, laden/unladen	km/h	5.5/6.0	
5.2	Lift speed, laden/unladen	m/s	0.100/0.130	
5.3	Lowering speed, laden/unladen	m/s	0.180/0.165	
5.4	Reaching speed, laden/unladen	m/s	0.115/0.165	
5.8	Max.gradeability, laden/unladen	%	6/10	
5.10	Service brake		Electromagnetic braking	
6.1	Drive motor rating S2 60 min	kW	1.5	
6.2	Lift motor rating at S3 15%	kW	3	
6.4	Battery voltage/nominal capacity K5	V/Ah	24/280	
6.5	Battery weight	kg	280	
8.1	Type of drive control		AC CURTIS	
10.5	Steering design		AC ZAPI	


1.2t/1.6t Mast specification

Type	Fork lift height h3	Mast lowered h1	Mast extended h4	Free lift height	Capacity	
					Load capacity at 600mm	
Wide view mast	mm	mm	mm	mm	1.2t	1.6t
	2500	1940	3552	0	1200	1600
	2700	2040	3752	0	1200	1600
	3000	2190	4052	0	1200	1600
	3300	2340	4352	0	1200	1600
	3500	2440	4552	0	1200	1600
	3600	2490	4652	0	1200	1550
	3700	2540	4752	0	1200	1500
	3800	2590	4852	0	1200	1500
	4000	2790	5052	0	1200	1430
Wide view full free triplex mast	4300	2940	5352	0	1150	1360
	4500	3040	5552	0	1100	1300
	3500	1975	4552	923	1200	1600
	3700	2040	4752	988	1200	1500
	4000	2140	5052	1088	1200	1430
	4300	2240	5352	1188	1150	1360
	4500	2290	5552	1238	1100	1300
	4700	2390	5752	1338	1050	1220
	5000	2490	6062	1438	1000	1130
	5200	2540	6252	1488	930	1050
5500	2640	6552	1588	850	950	



A Series High Range Stand-on Pallet Stacker With Reach Fork

with capacities of 1,200 to 1,600kg



HANGCHA FORKLIFT CANADA INC.

Company address:
6-980 Rue Valois, Vaudreuil-Dorion,
QC, J7V 8P2, Canada

Toll Free: 877-319-HCFC (4232)
Landline: 450-319-HCFC

info@hcforkliftcanada.com
www.hcforkliftcanada.com



HANGCHA GROUP CO., LTD. reserves the right to make any changes without notice concerning colors, equipment, or specifications detailed in this brochure, or to discontinue individual models. The colors of trucks, delivered may differ slightly from those in brochures.

The World of Hangcha



A Series High Range Stand-on Pallet Stacker With Reach Fork

The A series pallet stacker with reach fork moves goods forward and backward with a scissor fork extension system. It acts as a counterbalanced stacker when its fork is extended, which can handle non-standard pallets, enclosed pallets, and enclosed shelves easily; and acts as a straddle stacker when its fork is retracted, which can operate flexibly in narrow passage.

Easy/ Efficiency/ Economy



High Performance

- / EPS (Electric Power Steering) system offer easier and more flexible operation.
- / The AC driving motor features excellent acceleration performance, outstanding climbing ability, low heat emission, and is brushless, and maintenance-free.
- / The latest CURTIS AC / ZAPI AC control system realizes accurate and stable control, and higher efficiency.
- / The CANBUS structure makes communication of the entire machine faster and more reliable.
- / Regenerative brake of the truck prevents it from sliding on a slope.
- / Switches, plug connectors, meters, and other important parts are all imported from abroad, with excellent performance and reliable quality.
- / Fork tilting function, and load backrest realize safer loading and unloading of goods.
- / The hydraulic power unit features low noise, small vibration, and stable and reliable lifting and lowering.

Comfort

- / The vibration-reduction design of the pedal reduces fatigue of long-duration operation.
- / New designed tiller has beautiful appearance, and function buttons for comfortable operation.
- / The standard configuration of tortoise speed driving function allows the truck to move at low speed more easily.

Reliability

- / All plug connectors are imported and waterproof, and all cables have reliable protection, which increases reliability of electrical system significantly.
- / Non-contact proximity switch features long service life and reliable operation.
- / Power plug is fastened to truck body, which can avoid damage of plug due to impact when battery is lifted for installation.
- / Flexible connections of the battery can avoid disconnection fault of battery because of lasting vibration.

Safety

- / Traveling speed will be automatically reduced after fork lifting 500mm.
- / Turning speed is automatically reduced when steering.
- / The integrated stamping molded guardrail offers better protection for the operator.
- / Release braking, reverse braking and emergency braking can ensure safety of traveling.
- / Anti-sliding function on slope can ensure safety of operation.
- / The belly button on top of operating tiller can avoid the driver from injury effectively.
- / The soft landing system reduces lowering speed automatically when height from ground to fork is less than 100mm, which provides effective protection for goods.

Maintenance

- / The brushless, maintenance-free AC driving motor reduces operation cost significantly.
- / The meter integrating battery indicator, timer, and fault self-diagnosis is convenient for maintenance.
- / Back cover can be opened fully, and all components and parts are clear at a glance, which is very convenient for maintenance of the entire machine.

Options

- / Mast height: 2500-4500mm for duplex mast, 3500-5500mm for triplex mast
- / Various fork lengths
- / Sideshift move LH/RH:60mm

Standard specification

- / AC driving motor
- / CURTIS / ZAPI controller for traction motor
- / Controller for pump motor
- / EPS (Electric Power Steering) system
- / Automatic deceleration at turns
- / Proportional speed regulation for all fork operations
- / Pedal and guardrail
- / Emergency power off switch
- / Multi-function battery condition meter
- / High-performance loading wheels
- / Fork length 1070mm
- / Adjustable outer distance of forks within the range of 200-896mm
- / Fork tilt forward / backward 3°/5°
- / Load backrest
- / 2.7m duplex mast with double lifting cylinders
- / Soft landing system
- / Multi-function tiller
- / Traveling speed will be automatically reduced after fork lifting 500mm
- / Reach distance of fork: 590mm
- / Battery capacity: 280Ah for 1.2t model, 340Ah for 1.6t model



Multi-function tiller



Forks move forward by the scissor structure



Back cover can be opened fully



Proportional controlled forks can be operated more accurately